FloodFence Wall Connector

PLSE317

Specifications

Weight	12.000000
Color	White
Composition	Mild Steel
Contents/Package	1 each
Dimensions	20 cm W x 58 cm D x 45 cm H
Sold as	0

Description

Lightweight, reusable system can be easily connected and deployed rapidly by one person, making it ideal to protect against flash flooding; does not require any pre-applied ballast

System self-balances, with each unit incorporating a slim line base gasket to allow an effective seal to hard-standing ground terrain

Ideal for controlling and deflecting flowing water, responding to flash floods from heavy rain, drain or river overflows, or for burst water mains; can also be used for fire water runoff control

When connected to other units, the effective linear length of each is 0.91m, and can be used for water flows up to 40cm deep

Corner (PLSE316) allows inner and outer corners to be deployed in conjunction with standard units — two connected units make an ‘outer’ corner; Wall Connector (PLSE317) allows barrier to connect to and seal against vertical surfaces; Outer Corner Locking Pin (PLSE318) locks two Corner Units together

New Pig Ltd.
Hogs Hill • Watt Place • Hamilton International Technology Park
Blantyre • Glasgow • United Kingdom • G72 0AH

+44 (0)800 919 900

New Pig B.V.
Concorde 5 • 5126 RM Gilze • The Netherlands

+31 (0)76 596 9250 (English)
+33 (0)800 90 30 22 (French)
+49 (0)800-1-827-487 (German)
+39 800 874 60 (Italian)

newpig.co.uk
pigpen@newpig.com

newpig.eu
pigpost@newpig.com